## EXA POS











Portrait Display



VESA Mount Capable\*



Cable Cover for Extra Protection



\* Mounting poles/brackets/kiosk stand are not included



SPECIFICATIONS	EXA POS J624/J627	EXA POS A524/A527
PROCESSOR	Intel Quad Core Celeron J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Rockchip RK3568, Quad core Cortex-A55, up to 2.0 GHz
SYSTEM MEMORY	8 GB DDR4 RAM	4 GB DDR4 RAM
STORAGE	1 x 128 GB 2.5" SATA SSD	32 GB eMMC
DISPLAY		
SIZE / RESOLUTION	23.8"/27" TFT LCD / 1920 x 1080 pixels	23.8"/27" TFT LCD / 1920 x 1080 pixels
BRIGHTNESS	250 / 300 cd/m <sup>2</sup>	250 / 300 cd/m <sup>2</sup>
TOUCH SCREEN PANEL	Projected capacitive touch (10-point, multi-touch)	
I/O INTERFACE		
USB PORT	4 x USB 2.0	2 x USB 2.0
AUDIO PORT	1 x 3.5 mm mic-in / line-out, 2 x 5 W speaker	
NETWORK PORT	1 x RJ45 10/100/1000 Mbps	1 x RJ45 10/100/1000 Mbps
OPERATING SYSTEM		
WINDOWS	10 loT / 10 Pro / 11 loT / 11 Pro	Android 11
ENVIRONMENT & MECHANICAL	. SPECIFICATIONS	
DIMENSIONS & WEIGHT	24": 571 (W) x 349 (H) x 57 (D) mm   8.1 kg (without stand) 27": 650 (W) x 388 (H) x 56 (D) mm   8.5 kg (without stand)	
VESA PATTERN	100 x 100 mm	100 x 100 mm
TEMPERATURE	Operating: 0°C to 40°C	Storage: -20°C to 60°C
HUMIDITY	Operating: 20% to 80% (non-condensing)	Storage: 10% to 90% (non-condensing)
POWER CONSUMPTION	DC output: 12 V / 5 A   AC input: 100 V to 240 V, 50/60Hz	
MODEL OPTIONS		
MOUNTING TYPE	Desktop base / Freestanding base / VESA mount	
WIRELESS LAN	Integrated 802.11 b/g/n/ac	

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

## **The Senor Building**

65 & 67 Weaver Street Coopers Plains QLD 4108, Australia www.senortech.com.au P: +61 7 3275 5888 sales@senortech.com.au



Quality. Safety. Versatility.