

KDS



Fanless & Ventless
Aluminium Die-Cast Casing

* Optional



Internal Power Supply



Wireless LAN*

SENIOR



SPECIFICATIONS

	KDS 1200 (15")	KDS 1270 (17")
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	
SYSTEM MEMORY	8 GB DDR4 RAM (up to 32 GB)	
STORAGE	1 x M.2 PCIe 2280 SSD 1 x M.2 SATAIII 2242 SSD expansion socket	

DISPLAY

	KDS 1200 (15")	KDS 1270 (17")
SIZE	15" TFT LCD	17" TFT LCD
RESOLUTION	1024 x 768 pixels	1024 x 768 pixels
BRIGHTNESS	350 cd/m ²	350 cd/m ²
SCREEN TYPE	KDS1200G: 6H hardness tempered glass KDS1200T: Senor 5-wire resistive touch KDS1200PCT: Projected capacitive touch	KDS1270G: 6H hardness tempered glass KDS1270T: Senor 5-wire resistive touch

I/O INTERFACE

USB PORT	2 x USB 2.0, 3 x USB 3.0
SERIAL PORT	Up to 3 x DB9/RJ50
NETWORK PORT	1 x RJ45 10/100/1000 Mbps
CASH DRAWER PORT	1 x RJ12 (24 V)
VIDEO PORT	1 x HDMI
AUDIO PORT	1 x 3.5 mm Mic in / Line out 2 x 2W speaker

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11 IoT
---------	--------------------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	389 (W) x 334 (H) x 96 (D) mm 8.5 kg	446 (W) x 388 (H) x 118 (D) mm 11 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing	
VESA PATTERN	75 x 75 mm / 100 x 100 mm	
SAFETY CERTIFICATION & IP RATING	IP66 compliant	
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C	
HUMIDITY	Relative: 10% to 90% (non-condensing)	
POWER CONSUMPTION	DC output: 12 V / 5 A 60 W (max.) AC input: 100 V to 240 V	DC output: 12 V / 6 A 72 W (max.) AC input: 100 V to 240 V

MODEL OPTIONS

WIRELESS LAN	Integrated Wi-Fi 802.11 b/g/n (1T1R)
--------------	--------------------------------------

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.