

KDS 21

Kiosk Display System




IP66 Whole Unit



VESA Mount Capable*



Tool-free SSD Access



Internal Power Supply
Concealed Ports

* Mounting poles/brackets for VESA mount not included
Kiosk stands are not included

SENIOR



SPECIFICATIONS

	KDS J64	KDS T321
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Intel Dual Core i3-1215U 1.2 GHz (Turbo Boost up to 4.4 GHz)
SYSTEM MEMORY	1 x 8GB DDR4 RAM (up to 16 GB)	1 x 8GB DDR4 RAM (up to 32 GB)
STORAGE	1 x removable M.2 PCIe 2280 SSD	

DISPLAY

SIZE	21.5" TFT LCD (LED backlight)
RESOLUTION	1920 x 1080 pixels
BRIGHTNESS	250 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)

I/O INTERFACE

USB PORT	3 x USB 2.0, 1 x USB 3.0
SERIAL PORT	2 x RJ50
NETWORK PORT	1 x RJ45 10/100/1000 Mbps
CASH DRAWER PORT	1 x RJ12 (supports both 12 V & 24 V)
VIDEO & AUDIO PORT	1 x HDMI
SPEAKER	2 x 2 W

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11 IoT / 11 Pro
---------	-----------------------------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	519 (W) x 322 (H) x 46 (D) mm 8.0 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing
VESA PATTERN	100 x 100 mm
SAFETY CERTIFICATION & IP RATING	IP66 compliant
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C
HUMIDITY	Relative: 10% to 90% (non-condensing)
POWER CONSUMPTION	DC output: 19 V / 3.42 A 65 W AC input: 100 V to 240 V

MODEL OPTIONS

INTEGRATED CARD READERS	3-track MSR (Dual Head & Dual Directional)
WIRELESS LAN	Integrated Wi-Fi 802.11 b/g/n/ac, Bluetooth 4.1

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.