

Hecto POS



VESA Mount Capable[#]



Magnetic Cover Plate for Easy Cable Management



Removable 2.5" SSD



350% Better Performance
Intel Celeron J6412 (Win 11 Capable)

[#] Mounting poles/brackets are not included

SE^NOR



SPECIFICATIONS

Hecto POS J615

Hecto POS A616

PROCESSOR	Intel Quad Core Celeron J6412 2.0 GHz up to 2.6 GHz	Rockchip RK3576, Octa-core Cortex 4 x A72 + 4 x A53, up to 2.2 GHz
SYSTEM MEMORY	8 GB DDR4 RAM (up to 32 GB)	4 GB LPDDR4
STORAGE	1 x 128 GB removable 2.5" SATA SSD	32 GB eMMC

DISPLAY

SIZE / RESOLUTION	15" TFT LCD / 1024 x 768 pixels	15.6" TFT LCD / 1920 x 1080 pixels
BRIGHTNESS	350 cd/m ²	250 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)	Projected capacitive touch (multi-touch)

I/O INTERFACE

USB PORT	4 x USB 3.0, 2 x USB 2.0	2 x USB 3.0, 2 x USB 2.0
SERIAL PORT	3 x RJ50 (0/5/12 V selectable by jumper)	1 x RJ11 (DB9 adapter included)
VIDEO PORT	1 x VGA	1 x mini HDMI
AUDIO PORT	2 x 2 W mic-in / line-out (combined)	2 x 2 W speaker
NETWORK PORT	1 x RJ45 10/100/1000 Mbps	1 x RJ45 10/100/1000 Mbps
CASH DRAWER PORT	1 x RJ12 (24 V by default optional 12 V by jumper)	1 x RJ12 (12 V)

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11 IoT / 11 Pro	Android 11.0
---------	-----------------------------------	--------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	360 (W) x 330 (H) x 190 (D) mm 4.7 kg	385 (W) x 308 (H) x 190 (D) mm 3.8 kg
CHASSIS MATERIAL	Base & chassis: aluminium die-cast	Base: aluminium die-cast Chassis: ABS
VESA PATTERN	100 x 100 mm	
TEMPERATURE	Operating: 0°C to 35°C Storage: -15°C to 60°C	
HUMIDITY	Operating: 20% to 85% Storage: 20% to 85% (non-condensing)	
POWER CONSUMPTION	12 V / 5 A, external power adapter, 100-240 V, 50/60 Hz	

MODEL OPTIONS

INTEGRATED CARD READER	3-track MSR	
CUSTOMER DISPLAY	8"/10"/15" TFT LCD display	11.6"/15.6" TFT LCD display

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au



Quality. Safety. Versatility.