


HPC X6A

Rugged Handheld PC



High Brightness LCD 670 Nits
6.5" 720 x 1612 Pixels



Optimised Performance
Octa-core Processor + 8 GB RAM



Rugged Design
IP68 Whole Unit
MIL-STD-810H Certified



5,800 mAh Battery
Up To 16 Hours
Operation Time

SE~~N~~OR



SPECIFICATIONS

HPC X6A

PROCESSOR	MediaTek Helio G99 (ARM Octa-Core Cortex® - 2*A76 2.2 GHz + 6*A55 2.0 GHz)
SYSTEM MEMORY	8 GB LPDDR4 RAM
STORAGE	128 GB eMMC

DISPLAY

SIZE / RESOLUTION	6.56" IPS TFT LCD / 720 x 1612 pixels
BRIGHTNESS	670 cd/m ²
TOUCH SCREEN PANEL	5-point projected capacitive touch (Corning Gorilla 7H hardness)

I/O INTERFACE

USB PORT	1 x USB Type-C
WWAN SIM CARD	LTE FDD: B1/2/3/4/5/7/8/12/13/17/18/19/20//25/26/28A/28B/30/66 LTE TDD: B34/38/39/40/41 WCDMA: B1/2/4/5/8 GSM: B2/3/5/8
WI-FI & BLUETOOTH	Wi-Fi 802.11 a/b/g/n/ac 2.4 GHz & 5.0 GHz, Bluetooth 5.1
AUDIO	1 x 1 W speaker
2D SCANNER	Zebra 4710 Barcode Reader, optional long range up to 10 metres
RFID READER	NFC 13.56 MHz, supports ISO/IEC 14443A/14443B/15693/18092/Mifare

OPERATING SYSTEM

ANDROID	14 with GMS certified
---------	-----------------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	170.2 (W) x 80.7 (H) x 14 (D) mm 311 g
BATTERY	Battery capacity: 5,800 mAh (built-in) Working time: up to 16 hours
CAMERAS	Front: 32.0 MP Rear Main: 48 MP, AF + PDAF 8 MP wide-angle 2 MP Macro
SENSORS	Gravity Acceleration Sensor
IP RATING	IP68 whole unit
DROP RESISTANCE	MIL-STD-810H (1.5M to plywood)
TEMPERATURE	Operating: -20°C to 60°C Storage: -30°C to 70°C
HUMIDITY	Operating: RH95% non-condensing
POWER CONSUMPTION	Power adaptor input: DC 100-240 V, 50/60 Hz PD 20 W

MODEL OPTIONS

CHARGING DOCK	5 V, 2 A, POGO pin connection for easy docking
---------------	--

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au



Quality. Safety. Versatility.