


EXA POS



Portrait Display



VESA Mount Capable*



Cable Cover
for Extra Protection

* Mounting poles/brackets/kiosk stand are not included

SE-NOR



SPECIFICATIONS

EXA POS J624/J627

EXA POS A524/A527

PROCESSOR	Intel Quad Core Celeron J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Rockchip RK3568, Quad core Cortex-A55, up to 2.0 GHz
SYSTEM MEMORY	8 GB DDR4 RAM	4 GB DDR4 RAM
STORAGE	1 x 128 GB 2.5" SATA SSD	32 GB eMMC

DISPLAY

SIZE / RESOLUTION	23.8"/27" TFT LCD / 1920 x 1080 pixels	23.8"/27" TFT LCD / 1920 x 1080 pixels
BRIGHTNESS	250 / 300 cd/m ²	250 / 300 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (10-point, multi-touch)	

I/O INTERFACE

USB PORT	4 x USB 2.0	2 x USB 2.0
AUDIO PORT	1 x 3.5 mm mic-in / line-out, 2 x 5 W speaker	
NETWORK PORT	1 x RJ45 10/100/1000 Mbps	1 x RJ45 10/100/1000 Mbps

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11 IoT / 11 Pro	Android 11
---------	-----------------------------------	------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	24": 571 (W) x 349 (H) x 57 (D) mm 8.1 kg (without stand) 27": 650 (W) x 388 (H) x 56 (D) mm 8.5 kg (without stand)	
VESA PATTERN	100 x 100 mm	100 x 100 mm
TEMPERATURE	Operating: 0°C to 40°C	Storage: -20°C to 60°C
HUMIDITY	Operating: 20% to 80% (non-condensing) Storage: 10% to 90% (non-condensing)	
POWER CONSUMPTION	DC output: 12 V / 5 A AC input: 100 V to 240 V, 50/60Hz	

MODEL OPTIONS

MOUNTING TYPE	Desktop base / Freestanding base / VESA mount
WIRELESS LAN	Integrated 802.11 b/g/n/ac

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.