



v6POS



IP54 Whole Unit



Fanless & Screwless



2 x Removable M.2 SSD

SENOR

SENROR v6POS Series Touch POS Terminal


Senor v6POS series feature a brand new concept with an **ultra-narrow bezel-less screen** and **sleek exterior design**, with coloured frame and casing to match the retailer's style.



v6POS is an **energy-efficient solution** with low power consumption on a high-performing platform. The CPU consumes less power, generates less heat and helps to keep our environment green.

With its **elegant design**, v6POS is ideally suited for the retail and hospitality industries' flagship and pop-up stores.

I/O Connector



v6POS Standard Type

3 x Serial | 1 x LAN | 6 x USB
1 x Cash Drawer | 1 x HDMI

Optional Accessories



Wireless LAN



9.7" / 15" Customer Display



Upward* / Downward
Customer Display



MSR / Fingerprint
/ RFID Reader



Coloured Frame* / Housing*



VFD Customer Display

Features



90 Degree Panel Tilt



Internal Power Supply
Cable Management System



Fanless / Screwless

* Coloured units & upward customer display are by special order only.



SPECIFICATIONS		v6POS T515	v6POS T715
PROCESSOR	Intel Core i5-1235U 1.3 GHz (Turbo Boost up to 4.4 GHz)		Intel Core i7-1255U 1.7 GHz (Turbo Boost up to 4.7 GHz)
SYSTEM MEMORY	8 GB DDR4 RAM (up to 64 GB)		8 GB DDR4 RAM (up to 64 GB)
STORAGE DEVICE	1 x 128 GB removable M.2 PCIe 2280 SSD 1 x 128 GB M.2 PCIe 2280 expansion socket (supports RAID 0/1/5/10)		
DISPLAY			
SIZE / RESOLUTION	15" TFT LCD (LED backlight) / 1024 x 768 pixels		
BRIGHTNESS	350 cd/m²		
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)		
I/O INTERFACE (STANDARD)			
USB PORT	6 x USB 2.0 1 x USB 3.0 (front panel)		
SERIAL PORT	3 x RJ50		
VIDEO PORT	1 x HDMI 1.4		
AUDIO PORT	2 x built-in speakers 1 x 3.5 mm Mic-in/Line-out		
CASH DRAWER PORT	1 x RJ11 (24 V)		
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps (up to 2 x Ethernet ports)		
OPERATING SYSTEM			
WINDOWS	10 IoT / 10 Pro / 11 IoT / 11 Pro		
ENVIRONMENT & MECHANICAL SPECIFICATIONS			
DIMENSIONS & WEIGHT	366 (W) x 290 (H) x 193 (D) mm 7.8 kg		
CHASSIS MATERIAL	Die-cast aluminium		
IP RATING	IP54 whole unit		
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C		
HUMIDITY	Operating: 0% to 80% Storage: 10% to 90% (non-condensing)		
POWER CONSUMPTION	12 V / 6 A, internal power adapter, 100-240 V, 50/60 Hz		
MODEL OPTIONS			
INTEGRATED READERS	3-track MSR, RFID (125 kHz / 13.56 MHz), Fingerprint reader, 2D barcode reader		
CUSTOMER DISPLAY	2-line VFD or 9.7" / 15" TFT LCD (optional touch)		
WIRELESS LAN	Integrated 802.11 b/g/n/ac + Bluetooth 4.1		
COLOURED FRAME	Black (standard) White/Red/Green/Blue/Purple (special order)		
COLOURED UNIT	Black (standard) Gold/Silver (special order)		

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au



Quality. Safety. Versatility.