

x3POS



VESA Mount Capable



Compact 11.6"
Space-saving



IP54 Whole Unit

SENIOR



SPECIFICATIONS	x3S J64	x3S T312
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Intel Dual Core i3-1215U 1.2 GHz (Turbo Boost up to 4.4 GHz)
SYSTEM MEMORY	8 GB DDR4 RAM	8 GB DDR4 RAM
STORAGE DEVICE	1 x 128 GB removable M.2 PCIe 2280 SSD / 1 x 128 GB removable M.2 SATA 2280 SSD	
DISPLAY		
SIZE / RESOLUTION	11.6" TFT LCD (LED backlight) / Full HD 1920 x 1080 pixels	
BRIGHTNESS	300 cd/m ²	
TOUCH SCREEN PANEL	Projected capacitive touch (multi-touch)	
I/O INTERFACE		
USB PORT	5 x USB 2.0, 1 x USB 3.0 (side)	
SERIAL PORT	2 x RJ50	
AUDIO PORT	2 x 2 W speakers	
CASH DRAWER	1 x RJ12 (24 V)	
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps	
OPERATING SYSTEM		
WINDOWS	10 IoT (64-bit) / 10 Pro (64-bit) / 11 IoT (64-bit) / 11 Pro (64-bit)	
LINUX	Kernel 3.0 up	
ENVIRONMENT & MECHANICAL SPECIFICATIONS		
DIMENSIONS & WEIGHT	285 (W) x 44~376 (H) x 195 (D) mm 4.5 kg	
CHASSIS MATERIAL	Aluminium die-cast & Polycarbonate-ABS	
IP RATING	IP54 whole unit	
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C	
HUMIDITY	10% to 90% (non-condensing)	
POWER CONSUMPTION	19 V / 3.15 A, external power adaptor, 100-240 V, 50/60 Hz 19 V / 6.31 A, external power adaptor, 100-240 V, 50/60 Hz (printer integrated)	
MODEL OPTIONS		
INTEGRATED READERS	3-track MSR, Fingerprint reader, RFID, 2D barcode reader	
CUSTOMER DISPLAY	11.6" (1980 x 1080) LCD or 2-line VFD	
WIRELESS LAN	Integrated Dual Band Wi-Fi 802.11 b/g/n/ac (2x2 MIMO) + Bluetooth 4.1	
COLOURS	Dark Grey (standard) White (optional)	

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
sales@senortech.com.au



Quality. Safety. Versatility.