# **ISPOS 10**





Wall Mount Capable



IP66 Whole Unit\*



**VESA Mount Capable** 



**iSPOS 10 Series Vast Potential in Limited Space** 

The iSPOS 10 Series brings to you Senor's unparalleled quality and durability standard in a **compact-sized all-in-one** solution.

Its 10.4" high brightness, high resolution LED screen with multi-touch support offers the user comfort and ease on a fully functional surface. Powered by Intel® Quad Core Celeron J6412 Elkhart Lake platform and fitted with SSD storage, the iSPOS 10 Series exhibits superior performance and reliability to manage high volume transactions effectively.





A wide array of **integrated options** for seamless and wireless communication ensures the system is well connected.

The iSPOS 10 Series can be implemented for a diverse range of applications in the **retail**, **hospitality**, **banking and industrial sectors**.

## iSPOS 10 Series Sleek Wall Mount Panel PC

The wall mount solution, iSPOS 10 Series is ideally suited for sites with restricted space that require multiple access points for self-service activities.

#### Ideal application for

- Kitchen bump screen
- · Guests check-in
- Membership registration
- Information operator
- · Warehouse management
- Government facilities





Nano Coating & Rubber Seals -:

Hydrophobic & grease-repelling



#### · Fanless & Ventless

IP66 rated water/dust resistance

#### **Aluminium Die-cast Casing**

Robust & durable

#### **Concealed I/O Ports**

Enhanced water resistance

Internal Power Supply -

Secured protection



**VESA Mount Capable** 

75x75 mm / 100x100 mm

### **iSPOS 10 Series Options**



2-line VFD (custom order)



MSR/RFID



802.11 ac + BT V4.2



	10000 0440
SPECIFICATIONS	iSPOS 6410
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)
SYSTEM MEMORY	8 GB DDR4L RAM (up to 32 GB)
STORAGE DEVICE	128 GB M.2 2280 SSD
DISPLAY	
SIZE / RESOLUTION	10.4" LED / 1024 x 768 pixels
BRIGHTNESS	400 cd/m <sup>2</sup>
TOUCH SCREEN PANEL	Projected capacitive touch
I/O INTERFACE	
USB PORT	4 x USB 2.0 (up to 6 x USB 2.0)
SERIAL PORT	2 x DB9 (up to 4 x DB9)
VIDEO PORT	Up to 1 x HDMI (by order)
AUDIO PORT	2 x built-in speakers
ETHERNET PORT	1 x Gigabit LAN 10/100/1000 Mbps
OPERATING SYSTEM	
WINDOWS	10 IoT / 10 Pro / 11 IoT
ENVIRONMENT & MECHANICAL S	PECIFICATIONS
DIMENSIONS & WEIGHT	Desktop: 276 (W) x 230 (H) x 165 (D) mm   3.0 kg Wall Mount: 276 (W) x 223 (H) x 42 (D) mm   3.0 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing with nano-coating technology
VESA PATTERN	75 x 75 mm / 100 x 100 mm
IP RATING	IP66
	1700
TEMPERATURE	Operating: 0°C to 40°C   Storage: -20°C to 60°C
TEMPERATURE HUMIDITY	***
	Operating: 0°C to 40°C   Storage: -20°C to 60°C
HUMIDITY	Operating: 0°C to 40°C   Storage: -20°C to 60°C  Operating: 0% to 80%   Storage: 10% to 90% (non-condensing)
HUMIDITY POWER CONSUMPTION	Operating: 0°C to 40°C   Storage: -20°C to 60°C  Operating: 0% to 80%   Storage: 10% to 90% (non-condensing)

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

#### **The Senor Building**

65 & 67 Weaver Street Coopers Plains QLD 4108, Australia www.senortech.com.au P: +61 7 3275 5888 sales@senortech.com.au



Quality. Safety. Versatility.