iSPOS 10

VESA Mount Capable

IP66 Whole Unit *

Wall Mount Capable

* Desktop type only

SENOR

iSPOS 10 Series
Vast Potential in Limited Space

The iSPOS 10 Series brings to you Senor's unparalleled quality and durability standard in a **compact-sized all-in-one** solution.

Its 10.4″ high brightness, high resolution LED screen with multi-touch support offers the user comfort and ease on a fully functional surface. Powered by Intel® Quad Core Celeron J6412 Elkhart Lake platform and fitted with SSD storage, the iSPOS 10 Series exhibits **superior performance and reliability** to manage high volume transactions effectively.

A wide array of **integrated options** for seamless and wireless communication ensures the system is well connected.

The iSPOS 10 Series can be implemented for a diverse range of applications in the **retail, hospitality, banking and industrial sectors**.

iSPOS 10 Series
Sleek Wall Mount Panel PC

The wall mount solution, iSPOS 10 Series is ideally suited for sites with restricted space that require multiple access points for self-service activities.

Ideal application for

- Kitchen bump screen
- Guests check-in
- Membership registration
- Information operator
- Warehouse management
- Government facilities

Key Features

Fanless & Ventless
IP66 rated water/dust resistance

Nano Coating & Rubber Seals
Hydrophobic & grease-repelling

Aluminium Die-cast Casing
Robust & durable

Concealed I/O Ports
Enhanced water resistance

Internal Power Supply
Secured protection

VESA Mount Capable
75x75 mm / 100x100 mm

iSPOS 10 Series Options

2-line VFD
(custom order)

MSR/RFID

802.11 ac + BT V4.2

SPECIFICATIONS	iSPOS J610
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)
SYSTEM MEMORY	8 GB DDR4L RAM (up to 32 GB)
STORAGE DEVICE	128 GB M.2 2280 SSD

DISPLAY

SIZE / RESOLUTION	10.4" LED / 1024 x 768 pixels
BRIGHTNESS	400 cd/m^2
TOUCH SCREEN PANEL	Projected capacitive touch

I/O INTERFACE

USB PORT	4 x USB 2.0 (up to 6 x USB 2.0)
SERIAL PORT	2 x DB9 (up to 4 x DB9)
VIDEO PORT	Up to 1 x HDMI (by order)
AUDIO PORT	2 x built-in speakers
ETHERNET PORT	1 x Gigabit LAN 10/100/1000 Mbps

OPERATING SYSTEM

WINDOWS	10 IoT / 10 Pro / 11 IoT

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	Desktop: 276 (W) x 230 (H) x 165 (D) mm	3.0 kg Wall Mount: 276 (W) x 223 (H) x 42 (D) mm	3.0 kg
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing with nano-coating technology
VESA PATTERN	75 x 75 mm / 100 x 100 mm
IP RATING	IP66
TEMPERATURE	Operating: 0°C to 40°C	Storage: -20°C to 60°C
HUMIDITY	Operating: 0% to 80%	Storage: 10% to 90% (non-condensing)
POWER CONSUMPTION	19 V / 2.36 A, internal power adaptor, 100-240 V, 50/60 Hz

MODEL OPTIONS

INTEGRATED CARD READER	3-track MSR, RFID (125 kHz/13.56 MHz)
WIRELESS LAN	Wi-Fi 802.11 b/g/n/ac, BT V4.2

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

SENOR
TOUCH SCREEN SOLUTIONS
Quality. Safety. Versatility.