





ISPOS







The iSPOS is a mix of contemporary design and great functionality

Stay ahead of the competition with Senor's fanless and ventless all-in-one touch screen POS system, the iSPOS. Enclosed in a heat-dissipating solid aluminum die-cast casing, the iSPOS offers innovation and precision at its finest.

The iSPOS has undergone stringent industrial testing to Ingress Protection standards and awarded a rating of IP66, certifying high protection against liquid and dust particles to provide for **durability and sustainability** that is unparalleled by others.







Resistive Screen



Ergonomic Base

Built with the user in mind, the iSPOS offers an ergonomic design that is contrived to the natural movement of the human body ensuring compatibility and optimizing comfort level for the user.

The iSPOS provides for enhanced safety features such as concealed mounting hardware and internal cable management, alongside an elegant design giving your point of sale hardware a professional and state of the art finish.

iSPOS WP: Maximum Impact, Minimal Clutter

Space is no longer an issue with the ultimate all-in-one POS solution, the iSPOS WP. Stylish in construction and packed full of features, the iSPOS WP brings to you all the functions of the iSPOS and add to it an inbuilt thermal printer concealed within a sleek enclosure.

The ISPOS WP offers a polished design with minimal clutter.

A complete solution made uncomplicated.

Providing Superior User Safety and Peace of mind.



Key Features Removable SSD Easy Maintenance **Aluminium Die-cast Casing** Robust & Durable **IP66 Whole Unit** Water & Dust Resistance 70° Tilt & Lock Screen Stable & Sturdy





MSR / Smart Card Reader Fingerprint Reader / RFID Reader



270° Swivel Base Ergonomic Design

2-line VFD / 10" / 15" LCD Customer Display



Internal Power Supply
Secured Protection

Wireless Capability



SIZE / RESOLUTION 15° TFT LCD / 1024 x 768 pixels	SPECIFICATIONS	iSPOS 1200	iSPOS T715	
DISPLAY SIZE / RESOLUTION 15° TFT LCD / 1024 x 768 pixels BRIGHTNESS 350 cd/m² TOUCH SCREEN PANEL Resistive touch / Projected capacitive touch I/O INTERFACE USB PORT Front: 1 x USB 3.0 Back: 2 x USB 3.0, 2 x USB 2.0 SERIAL PORT 2 x DB9 (up to 3 x DB9/RJ50) 2 x DB9 (up to 3 x DB9) VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IOT / 10 Pro / 11 IOT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: 20°C to 60°C HUMIDITY Operating: 0°C to 40°C Storage: 20°C to 60°C HUMIDITY Operating: 0°C to 40°C Storage: 20°C to 60°C HUMIDITY Operating: 0°C to 40°C Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	PROCESSOR			
DISPLAY SIZE / RESOLUTION 15° TFT LCD / 1024 x 768 pixels BRIGHTNESS 350 cd/m² TOUCH SCREEN PANEL Resistive touch / Projected capacitive touch I/O INTERFACE USB PORT Front: 1 x USB 3.0 Back: 2 x USB 3.0, 2 x USB 2.0 SERIAL PORT 2 x DB9 (up to 3 x DB9/RJ50) 2 x DB9 (up to 3 x DB9) VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IOT / 10 Pro / 11 IOT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING 1P66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: 20°C to 60°C HUMIDITY Operating: 0°C to 40°C Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	SYSTEM MEMORY	8 GB DDR4 RAM (up to 32 GB)	8 GB DDR4 RAM (up to 64 GB)	
SIZE / RESOLUTION 15° TFT LCD / 1024 x 768 pixels BRIGHTNESS 350 cd/m² TOUCH SCREEN PANEL Resistive touch / Projected capacitive touch I/O INTERFACE USB PORT Front: 1 x USB 3.0 Back: 2 x USB 3.0, 2 x USB 2.0 SERIAL PORT 2 x DB9 (up to 3 x DB9/RJ50) 2 x DB9 (up to 3 x DB9) VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IOT / 10 Pro / 11 IOT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heal-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0°C to 40°C Storage: -10% to 90% (non-condensing) POWER CONSUMPTION 1 2 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	STORAGE DEVICE	1 x removable M.2 PCIe 2280 SSD, 1 x removable M.2 SATA 2280 SSD		
BRIGHTNESS 350 cd/m² TOUCH SCREEN PANEL Resistive touch / Projected capacitive touch I/O INTERFACE USB PORT Front: 1 x USB 3.0 Back: 2 x USB 3.0, 2 x USB 2.0 SERIAL PORT 2 x DB9 (up to 3 x DB9/RJ50) 2 x DB9 (up to 3 x DB9) VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IOT / 10 Pro / 11 IOT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP 66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 KHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	DISPLAY			
TOUCH SCREEN PANEL Resistive touch / Projected capacitive touch I/O INTERFACE USB PORT Front: 1 x USB 3.0 Back: 2 x USB 3.0, 2 x USB 2.0 SERIAL PORT 2 x DB9 (up to 3 x DB9/RJ50) 2 x DB9 (up to 3 x DB9) VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IoT / 10 Pro / 11 IoT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP 66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	SIZE / RESOLUTION	15" TFT LCD / 1024 x 768 pixels		
USB PORT Front: 1 x USB 3.0 Back: 2 x USB 3.0, 2 x USB 2.0 SERIAL PORT 2 x DB9 (up to 3 x DB9/RJ50) 2 x DB9 (up to 3 x DB9) VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IoT / 10 Pro / 11 IoT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP 66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0°C to 40°C Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	BRIGHTNESS	350 cd/m²		
SERIAL PORT 2 x DB9 (up to 3 x DB9/RJ50) 2 x DB9 (up to 3 x DB9/RJ50) VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IoT / 10 Pro / 11 IoT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0°C to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	TOUCH SCREEN PANEL	Resistive touch / Projected capacitive touch		
SERIAL PORT 2 x DB9 (up to 3 x DB9/RJ50) 2 x DB9 (up to 3 x DB9) VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IoT / 10 Pro / 11 IoT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP 66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	I/O INTERFACE			
VIDEO PORT 1 x HDMI AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IoT / 10 Pro / 11 IoT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP 66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	USB PORT	Front: 1 x USB 3.0 Back: 2 x USB 3.0, 2 x USB 2.0		
AUDIO PORT 2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IoT / 10 Pro / 11 IoT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heal-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	SERIAL PORT	2 x DB9 (up to 3 x DB9/RJ50)	2 x DB9 (up to 3 x DB9)	
CASH DRAWER PORT 1 x RJ12 (24 V) ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 IoT / 10 Pro / 11 IoT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP RATING IP 66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	VIDEO PORT	1 x HDMI		
ETHERNET PORT 1 x RJ45 10/100/1000 Mbps OPERATING SYSTEM WINDOWS 10 10T / 10 Pro / 11 10T / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP 66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	AUDIO PORT	2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out		
OPERATING SYSTEM WINDOWS 10 IoT / 10 Pro / 11 IoT / 11 Pro ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	CASH DRAWER PORT	1 x RJ12 (24 V)		
ENVIRONMENT & MECHANICAL SPECIFICATIONS DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	ETHERNET PORT	1 x RJ45 10/100/1000 Mbps		
DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10° / 15° TFT LCD	OPERATING SYSTEM			
DIMENSIONS & WEIGHT 389 (W) x 369 (H) x 232 (D) mm 8.5 kg CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	WINDOWS	10 loT / 10 Pro / 11 loT / 11 Pro		
CHASSIS MATERIAL Heat-dissipating solid aluminium die-cast casing 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	ENVIRONMENT & MECHANICAL SP	PECIFICATIONS		
VESA PATTERN 75 x 75 mm / 100 x 100 mm IP RATING IP66 whole unit Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	DIMENSIONS & WEIGHT	389 (W) x 369 (H) x 232 (D) mm 8.5 kg		
IP RATING IP66 whole unit TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing		
TEMPERATURE Operating: 0°C to 40°C Storage: -20°C to 60°C HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	VESA PATTERN	75 x 75 mm / 100 x 100 mm		
HUMIDITY Operating: 0% to 80% Storage: 10% to 90% (non-condensing) 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	IP RATING	IP66 whole unit		
POWER CONSUMPTION 12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C		
MODEL OPTIONS INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	HUMIDITY	Operating: 0% to 80% Storage: 10% to 90% (non-condensing)		
INTEGRATED CARD READER 3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	POWER CONSUMPTION	12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz		
Smart card reader, Fingerprint reader CUSTOMER DISPLAY 2-line VFD / 10" / 15" TFT LCD	MODEL OPTIONS			
	INTEGRATED CARD READER	11		
WIRELESS LAN Integrated 802.11 b/g/n/ac, 2T2R + Bluetooth 5.0	CUSTOMER DISPLAY	2-line VFD / 10" / 15" TFT LCD	2-line VFD / 10" / 15" TFT LCD	
	WIRELESS LAN	Integrated 802.11 b/g/n/ac, 2T2R + Blueto	Integrated 802.11 b/g/n/ac, 2T2R + Bluetooth 5.0	

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street Coopers Plains QLD 4108, Australia www.senortech.com.au P: +61 7 3275 5888 sales@senortech.com.au

