





ISPOS







The iSPOS is a mix of contemporary design and great functionality

Stay ahead of the competition with Senor's fanless and ventless all-in-one touch screen POS system, the iSPOS. Enclosed in a heat-dissipating solid aluminum die-cast casing, the iSPOS offers innovation and precision at its finest.

The iSPOS has undergone stringent industrial testing to Ingress Protection standards and awarded a rating of IP66, certifying high protection against liquid and dust particles to provide for **durability and sustainability** that is unparalleled by others.







Resistive Screen



Ergonomic Base

Built with the user in mind, the iSPOS offers an ergonomic design that is contrived to the natural movement of the human body ensuring compatibility and optimizing comfort level for the user.

The iSPOS provides for enhanced safety features such as concealed mounting hardware and internal cable management, alongside an elegant design giving your point of sale hardware a professional and state of the art finish.

iSPOS WP: Maximum Impact, Minimal Clutter

Space is no longer an issue with the ultimate all-in-one POS solution, the iSPOS WP. Stylish in construction and packed full of features, the iSPOS WP brings to you all the functions of the iSPOS and add to it an inbuilt thermal printer concealed within a sleek enclosure.

The iSPOS WP offers a polished design with minimal clutter.

A complete solution made uncomplicated.

Providing Superior User Safety and Peace of mind.





Optional Accessories



MSR / Smart Card Reader Fingerprint Reader / RFID Reader



2-line VFD / 10" / 15" LCD Customer Display



Wireless Capability



SPECIFICATIONS	iSPOS 1200	iSPOS T715
PROCESSOR	Intel Celeron Quad Core J6412 2.0 GHz (Turbo Boost up to 2.6 GHz)	Intel Dual Core i7-1255U 1.7 GHz (Turbo Boost up to 4.7 GHz)
SYSTEM MEMORY	8 GB DDR4 RAM (up to 32 GB)	8 GB DDR4 RAM (up to 64 GB)
STORAGE DEVICE	1 x 128 GB removable M.2 PCIe 2280 SSD, 1 x 128 GB removable M.2 SATA 2280 SSD	
DISPLAY		
SIZE / RESOLUTION	15" TFT LCD / 1024 x 768 pixels	
BRIGHTNESS	350 cd/m ²	
TOUCH SCREEN PANEL	Resistive touch / Projected capacitive touch	
I/O INTERFACE		
USB PORT	Front: 1 x USB 3.0 Back: 2 x USB 3.0, 2 x USB 2.0	
SERIAL PORT	2 x DB9 (up to 3 x DB9/RJ50)	2 x DB9 (up to 3 x DB9)
VIDEO PORT	1 x HDMI	
AUDIO PORT	2 x 2 W built-in speakers / 1 x 3.5 mm mic in/line out	
CASH DRAWER PORT	1 x RJ12 (24 V)	
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps	
OPERATING SYSTEM		
WINDOWS	10 loT / 10 Pro / 11 loT / 11 Pro	
ENVIRONMENT & MECHANICAL S	PECIFICATIONS	
DIMENSIONS & WEIGHT	389 (W) x 369 (H) x 232 (D) mm 8.5 kg	
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing	
VESA PATTERN	75 x 75 mm / 100 x 100 mm	
IP RATING	IP66 whole unit	
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C	
HUMIDITY	Operating: 0% to 80% Storage: 10% to 90% (non-condensing)	
POWER CONSUMPTION	12 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz	
MODEL OPTIONS		
INTEGRATED CARD READER	3-track MSR, RFID (supports 125 kHz/13.56 MHz) Smart card reader, Fingerprint reader	
CUSTOMER DISPLAY	2-line VFD / 10" / 15" TFT LCD	
WIRELESS LAN	Integrated 802.11 b/g/n/ac, 2T2R + Bluetooth 5.0	

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street Coopers Plains QLD 4108, Australia www.senortech.com.au P: +61 7 3275 5888 sales@senortech.com.au

