v5WP





Removable SSD*



Aluminium Die-cast Sleek Enclosure



IP54 Whole Unit



Senor v5WP Series Intelligent Touch POS Terminal

Senor v5WP Series is designed to meet the functional requirements of the users as well as having the modern appeal to enhance varied ambiences of the operating environment.






The design concept complements a user's workflow and operation of the POS unit thereby increasing productivity and efficiency. A variety of POS peripherals is available, including optional customer display screen and tool free interchangeable coloured bezel.

With its **elegant design**, v5WP is ideally suited for the retail and hospitality industries' flagship and pop-up stores.

I/O Connector



v5WP J19

2 x DB9 | 1 x Cash Drawer | 4 x USB 1 x LAN | 1 x VGA



v5WP C20/X35

2 x DB9 | 1 x Cash Drawer | 6 x USB 2 x LAN | 1 x VGA



Features





SPECIFICATIONS	v5WP J19	v5WP C20	v5WP X35
PROCESSOR	Intel Quad Core J1900 2.0 GHz (up to 2.42 GHz)	Intel Dual Core Celeron 3955U 2.0 GHz	Intel Dual Core i3-6100U 2.3 GHz (with Intel HT)
SYSTEM MEMORY	4 GB DDR3L RAM (up to 8 GB)	4 GB DDR4 RAM (up to 32 GB)	4 GB DDR4 RAM (up to 32 GB)
STORAGE DEVICE	2 x M.2 SATA SSD 2 x Half Slim SATA SSD (up to 240 GB, supports RAID)		
DISPLAY			
SIZE / RESOLUTION	15" TFT LCD (LED backlight) / 1024 x 768 pixels		
BRIGHTNESS	300 cd/m ²	350 cd/m ²	350 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch		
I/O INTERFACE			
USB PORT	4 x USB 2.0	6 x USB 2.0	6 x USB 2.0
SERIAL PORT	2 x DB9		
VIDEO PORT	1 x VGA		
AUDIO PORT	2 x built-in speakers / 1 x 3.5 mm mic in/line out		
CASH DRAWER PORT	1 x RJ12 (24 V)		
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps	0 Mbps 2 x RJ45 10/100/1000 Mbps	
OPERATING SYSTEM			
WINDOWS	POSReady 7 / 7 Pro / 10 IoT / 10 Pro		
ENVIRONMENT & MECHANICAL SE	PECIFICATIONS		
DIMENSIONS & WEIGHT	366 (W) x 495 (H) x 245 (D) mm 10 kg		
CHASSIS MATERIAL	Die-cast aluminium		
IP RATING	IP54 whole unit		
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C		
HUMIDITY	Operating: 0% to 80% Storage: 10% to 90% (non-condensing)		
POWER CONSUMPTION	24 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz		
MODEL OPTIONS			
INTEGRATED CARD READERS	3-track MSR, RFID (125 kHz, 13.56 MHz), IC card reader		
CUSTOMER DISPLAY	VFD / 7" LCD / 10" LCD / 15" LCD		
INTEGRATED BARCODE READER	1D/2D barcode reader		
WIRELESS LAN	Integrated 802.11 b/g/n/ac + Bluetooth 4.1		
COLOURED FRAME	Black (standard) White / Red / Green / Purple / Teal Blue (special order)		
COLOURED UNIT	Black (standard) Silver (special order)		

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street Coopers Plains QLD 4108, Australia www.senortech.com.au P: +61 7 3275 5888 F: +61 7 3275 5800 sales@senortech.com.au

